



- Equipment & Controls list**
For extras & explanations please see listings sheets
- 1 PAIR GAM POSTS. (150mm Sq. BOX SECTION WITH DUCT ENTRY AND INSPECTION PLATES)
 - ADEQUATE 60mm ANTI-CRUSH FLEXIBLE DUCTING - SEPERATE RUNS TO EACH POST FROM M1
 - 1 PAIR GATES (SIZE APPROX 3600mm X 1800mm)
 - 1 PAIR OPEN BACK STOPS
 - 1 No. CENTRE STOP
 - 1 PAIR DOMESTIC UNDERGATE JACK OPERATORS
 - ADEQUATE SWA CABLES
 - ADEQUATE RBS CABLES
 - 1 No. C1 RADIO RECEIVER (HOUSED WITHIN FIBRE GLASS M1)
 - TBA QTY C2/3 HAND HELD RADIO CONTROLS
 - 2 No. C5 EXTERNAL PUSH BUTTONS ONE WITH TIMED ENTRY
 - 1 No. C6 CODED ENTRY PAD
 - 1 PAIR S1 SAFETY BEAMS - (S2 SAFETY LOOP, OPTIONAL EXTRAS)
 - 1 No. M1 ENCLOSURE COMPLETE, INCLUDING MICRO PROCESSOR CONTROLLER AND MAINS ISOLATION (13 AMP DEDICATED) Etc.
 - 1-1 M3 AUDIO LINK FACILITY
- NOTE :
VIDEO OPTIONAL AS ARE EXTENSIONS OF EITHER

NOTES IT IS STRONGLY RECOMMENDED THAT UNDERGATE OPERATORS ARE ONLY USED ON DOMESTIC LOW RISK OF ABUSE SYSTEMS

THE POSITION OF THE SUPPORT STEELS WILL DETERMINE THE AMOUNT OF LEAF SWING. IF MORE THAN 100° IS REQUIRED THE POSTS MAY BE SET BACK WITHIN OR BEHIND OPENING

Itemref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference
Designed by DBT	Checked by AJS	Approved by - date 14/09/01	Date 14/09/01
		File name STDGATES.DWG	Scale NTS
		DOMESTIC UNDERGATE Edition 0 Sheet 1/1	